



THE TELESIS GUIDE

A comprehensive overview of products and services from the permanent marking and traceability experts.

LASER MARKING SYSTEMS

PINSTAMP® DOT PEEN

TELESCRIBE® MARKING SYSTEMS

CUSTOM ENGINEERED SOLUTIONS



TELESIS IS



THE PIONEERS

While Telesis PINSTAMP® systems remain **the gold standard** in dot peen marking, our team consistently brings new game-changing products to market. Our Fiber laser markers introduced new technology to permanent marking and together with our Infrared, Green, UV, and CO2 markers continually push the boundaries of industrial marking. Forward-thinking Telesis-developed vision systems **create catalysts for industrial automation.**



RUGGED & RELIABLE

Telesis equipment is **built to last**. We engineer our laser marking systems and dot peen markers with **high-quality, robust materials** that stand up to the challenges of tough environments. Highest-quality laser sources, powder-coated metals, damage-proof screens, and sturdy materials are just some of the reasons our customers experience **fewer problems, less down time, and greater production efficiency.**

DIFFERENT



THE WIDEST ARRAY

Whether you need an off-the-shelf bench-top PINSTAMP® marker or want a custom engineered integrated laser system, **Telesis has the product lineup, the know-how, and specialized service offerings** to make it happen. Also, running all your marking equipment with the same great proprietary MERLIN® software **requires less employee training and more cross-functionality** in your operations.



ONE-STOP SHOP

Ditch the confused and fragmented individual service providers and **let us take care of everything.** From equipment, to software, to customization and integration, we'll design and fully support all aspects of a **turnkey solution that meets your unique needs.** Ongoing maintenance programs and on-call service will ensure your investment is **long lasting and always efficient.**



THE BEST PEOPLE

We take our customers seriously. Team Telesis is united by the mission of delivering the ultimate experience at every step of our customers' journeys. Whether you are working with the expert sales team, talking to our network of strategic partners, chatting with our customer service team, or designing a custom solution with our engineers, **you will be wowed by the dedication and knowledge** we possess.

Guide Contents

TELESIS
F301



Laser Marking Systems

Page **9**

PINSTAMP[®] Dot Peen

Page **33**

Telescribe[®] Marking Systems

Page **47**

Telesis Advantage

Page **51**

Custom Engineered Solutions

Page **56**

Customer Service & Support

Page **57**



Automotive

**Aerospace
& Defense**

**Medical
& Pharma**

Telesis Technologies is a trusted partner to the most demanding manufacturers across a **wide range of established and emerging industries.**


Foodpack



**Consumer
Products**



**Semiconductors
& Electronics**



Laser Marking Systems



*" All of your employees seem
to be willing and able to give
that 'little bit extra' to make
everything go right. "*

- Ed Reinemeyer, Federal-Mogul

Laser Marker Overview

Page **10**

Dual-Head Laser Marking System

Page **13**

Fiber Laser Markers // 1064 nm

Page **15**

Vanadate Laser Markers // 1064 nm

Page **17**

Green Laser Markers // 532 nm

Page **19**

UV Laser Markers // 355 nm

Page **21**

CO₂ Laser Markers // 10.6 μm

Page **25**

Laser Enclosures

Page **29**

Laser Marker Overview

Dual-Head



The innovative, patented Telesis dual-head laser system is **perfectly suited for advanced applications that require rapid processing**. The multi-head design of this laser offers the **unique ability to control two laser markers with the same controller**, reducing overall footprint and lowering the cost of operation. It is the industry's **only fiber laser system of its kind to be entirely air cooled and powered from a single-phase power outlet**.


Fiber




The Telesis Fiber laser marking system is the **most versatile marking technology** due to its **adaptability, minimal maintenance, and the total elimination of consumables** from the marking process. They are most used in metal and plastic processing industries for **precise and efficient direct marking** of parts and products. From automotive manufacturing through medical and security technology to electronics, Telesis Fiber delivers.



Plastics



Metals



Carbon Migration




Deep Marking


Ultraviolet




The 355 nm UV laser wavelength is versatile in marking a wide range of materials and **perfect for "cold marking" applications where heat-affected zones are not allowed**—the machine is **great for marking plastics and silicon materials without additives and can mark glass with a reduced risk of micro-fracture**. The very small high-quality beam spot makes **precision micro-marking with extremely sharp resolution** possible.




Plastics



Metals



Low Pigmentation




Organics

Green



The Telesis EV4GDS is a fiber-coupled, diode-pumped, solid-state (DPSS) green wavelength system. The laser beam characteristics are **optimized for applications that require high beam quality and stability**. The EV4GDS offers **extra power and speed**—the ideal choice for laser marking, scribing, and trimming. The robust mechanical and optical design of the Telesis EV4GDS **enables operation in an industrial environment where shock, vibration, and dust are a concern**.



Plastics



Metals




Delicate Materials



Difficult Materials

Technology Options

Vanadate



E-Series diode-pumped YAG and vanadate laser markers offer **improved beam quality, increased depth of focus, and higher peak powers** compared to fiber lasers—for fine marking, heat-sensitive materials (metal, foils, silicon, plastics, etc.) and **applications where high consistency is required.**



Plastics

Metals




Fine Detail

Carbon Migration

CO2




Proven CO2 systems provide a galvo-steered beam. It is an **excellent choice for heavy use and high-duty cycle environments** and is beneficial to **label and packing operations** as it removes the need for consumables and speeds process. **Equally capable at stationary bench-top use and mark-on-the-fly installations**, this machine can mark up to 1300 characters per second in automated environments.



Plastics

Painted Metals



Organics


Melted Mark

Vari-Z™ 3-Axis 3D Marking

Vari-Z™ 3-Axis Laser Markers are perfectly suited for advanced applications that require processing of non-flat parts, multiple planes, and uneven surfaces. The Telesis Vari-Z™ technology increases the focal range, eliminating the need for tooling changes while saving time and money.

AutoFocus

Additionally, the AutoFocus function option on available Vari-Z™ model lasers compensates for varying target heights.





Our **patented dual-head laser design** is an industry first. It eliminates downtime and creates more efficient throughput.

Manufacturer: Kentek 800-432-2323
1000000 11mm 100 11 1000000 100 11 1000000
111 111 111 111 111 111 111 111

Double the Capability with One Controller


DUAL-HEAD LASER MARKING SYSTEM

Increases throughput in high-speed and repetitive applications

Allows for the unique ability to **control two lasers from the same controller**

Saves floor space and reduces part handling by the operator

Creates unmatched marking efficiency and operating productivity




Models	
F30V	30 Watt
F50V	50 Watt
F100V	100 Watt

Controllers	
F16I	External PC
F16IE	Embedded PC

Technology Options
Vari-Z™ 3-Axis 3D/AutoFocus
Cognex™ In-line Vision
Mark-on-the-Fly Software

Software
Proprietary Merlin® 2H

Lens Configurations						Working Clearance	
Diameter	Marking Area						
100 mm	2.56 in	x	2.56 in	65 mm	x 65 mm	3.82 in	97 mm
160 mm	3.54 in	x	3.54 in	90 mm	x 90 mm	6.93 in	176 mm
163 mm	4.33 in	x	4.33 in	110 mm	x 110 mm	7.28 in	185 mm
254 mm	6.89 in	x	6.89 in	175 mm	x 175 mm	11.65 in	296 mm
330 mm	9.06 in	x	9.06 in	230 mm	x 230 mm	15.23 in	387 mm
350 mm	9.84 in	x	9.84 in	250 mm	x 250 mm	15.43 in	392 mm
420 mm	11.42 in	x	11.42 in	290 mm	x 290 mm	19.45 in	493 mm



DUAL-HEAD
FIBER
VANADATE
GREEN
UV
CO ₂
ENCLOSURES




Telesis Technologies **helped**
perfect fiber laser marking
technology—now the gold
standard in laser marking.

Cleaner Marks in Less Time

FIBER LASER MARKING SYSTEM

- Features superior beam technology for fast and efficient marking
- Contains high quality components that are ruggedly industrial and durable
- Outperforms higher powered systems
- Safe in non-climate controlled environments where shock, vibration, and dust are a concern



Models

F30V	30 Watt
F50V	50 Watt
F100V	100 Watt

Controllers

Model 6	External PC
F14A	Embedded PC

Technology Options

Vari-Z™ 3-Axis
iZONIT™ Vision System
TeleView™ Quality Control
Programmable Mounting Post

Software


Proprietary Merlin® II LS

Lens Configurations

Diameter	Marking Area				Working Clearance	
100 mm	2.56 in	x	2.56 in	65 mm x 65 mm	3.82 in	97 mm
160 mm	3.54 in	x	3.54 in	90 mm x 90 mm	6.93 in	176 mm
163 mm	4.33 in	x	4.33 in	110 mm x 110 mm	7.28 in	185 mm
254 mm	6.89 in	x	6.89 in	175 mm x 175 mm	11.65 in	296 mm
330 mm	9.06 in	x	9.06 in	230 mm x 230 mm	15.23 in	387 mm
350 mm	9.84 in	x	9.84 in	250 mm x 250 mm	15.39 in	391 mm
420 mm	11.42 in	x	11.42 in	290 mm x 290 mm	19.45 in	493 mm

Dimensions

w/o Vari-Z™	w/ Vari-Z™	
5.076 in	6.32 in	w/o Vari-Z™ 5.991 in 152.2 mm w/ Vari-Z™ 5.221 in 140.2 mm
128.9 mm	160.5 mm	
w/o Vari-Z™	w/ Vari-Z™	
22.791 in	26.311 in	
578.9 mm	668.3 mm	



DUAL-HEAD

FIBER


VANADATE

GREEN

UV

CO₂

ENCLOSURES





The EVCDS laser **creates a near infrared wavelength laser beam** using innovative technology.

Versatile Marking on a Range of Materials

VANADATE LASER MARKING SYSTEM

Low-cost engraving and annealing for a wide array of product materials including ferrous and non-ferrous metal, label materials, and silicon

Precise setting controls for fine-tuned application versatility: Engraving, annealing, surface marking, and color marking

Very small HAZ (heat-affected zone) provides additional **flexibility with heat-sensitive and delicate components**

Models

EVCDS

Technology Options

Vari-Z™ 3-Axis
Mark-on-the-Fly Technology
Programmable Mounting Post

Controllers

E15 External PC
E15E Embedded PC

Software

Proprietary Merlin® II LS




Lens Configurations

Diameter	Marking Area				Working Clearance	
100 mm*	2.56 in	x	2.56 in	65 mm x 65 mm	3.82 in	97 mm
160 mm*	4.33 in	x	4.33 in	110 mm x 110 mm	6.93 in	176 mm
160 mm	4.33 in	x	4.33 in	110 mm x 110 mm	7.13 in	181 mm
254 mm*	6.89 in	x	6.89 in	175 mm x 175 mm	11.65 in	296 mm
254 mm	6.89 in	x	6.89 in	175 mm x 175 mm	11.5 in	292 mm
330 mm*	9.06 in	x	9.06 in	230 mm x 230 mm	15.24 in	387 mm
420 mm*	11.42 in	x	11.42 in	290 mm x 290 mm	19.41 in	493 mm

* Premium Lens

Dimensions



DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES

A man with a mustache, wearing dark safety glasses and a dark blue long-sleeved shirt, is leaning over a workbench in a laboratory or industrial setting. He is looking down at a green laser marking system. The system consists of a green metal housing with a laser head that is emitting a bright green laser beam. The laser beam is focused on a small, rectangular metal part that is mounted on a perforated metal plate. The background shows a computer monitor displaying a software interface, various tools, and equipment on shelves. The overall lighting is dim, with the green laser light providing the primary illumination for the work area.

The powerful design of the Green
Laser Marking System **performs**
well in industrial environments
with vibration and dust.

Extra Power for Robust Applications

GREEN LASER MARKING SYSTEM (EV4GDS)

Provides cold marking for **ultra-fine and very soft marking on parts**

Great option for marking materials that usually react poorly to infrared wavelengths

Wonderful for **micro-marking**, like 2D matrix codes, as well as detailed graphic logos

Changes surface color for legible marks **without burning** the material



Models

EV4GDS

Technology Options

Mark-on-the-Fly Technology
Programmable Mounting Post

Controllers

E15 External PC
E15E Embedded PC

Software


Proprietary **Merlin® II LS**

Lens Configurations

Diameter	Marking Area				Working Clearance	
100 mm	2.17 in	x	2.17 in	55 mm x 55 mm	3.54 in	90 mm
160 mm	4.33 in	x	4.33 in	110 mm x 110 mm	6.93 in	176 mm
250 mm	6.69 in	x	6.69 in	170 mm x 170 mm	11.34 in	288 mm



Dimensions



DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES



UV/one™
ULTRA VIOLET
LASER MARKING SYSTEM

The UV/one **offers impressive all-in-one design and an incredible focal tolerance.**

Ultra-Crisp Marks on Challenging Materials

ALL-IN-ONE ULTRAVIOLET LASER MARKING

All-in-one marker/controller design **saves space** in your facility with a compact footprint for **easy integration** into production lines

Through suppressed heat effects, burrs and yellow tinting are eliminated, allowing for a **nearly perfect finish**

Completely eliminate day-to-day consumables and **reduce operational costs**



Models

UV/one

Technology Options

iZONIT™ Vision System

Mark-on-the-Fly Technology

Programmable Mounting Post

Configurations

Marking Area

5.9 in x 5.9 in 150 mm x 150 mm

Working Clearance

9.409 in 239 mm


Controllers

Fully Integrated

Software

Proprietary Merlin® II LS

Dimensions



DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES





The UVC marks plastics and silicone **without the need of additives** and marks glass with a **reduced risk of microfracture.**

Damage-Free Versatility

ULTRAVIOLET LASER MARKING SYSTEM

- Versatile in **marking a wide range** of materials
- Perfect for “cold marking,”** where heat-affected zones are damaging or aesthetically unacceptable
- Eliminates additives** when marking plastic or silicon materials
- Reduces risk of micro-fracture** when marking glass micro-mark electronics, circuit boards, microchips, solar panels, gemstones, and medical instruments



Models

UVC

Technology Options

- Vari-Z™ 3-Axis
- iZONIT™ Vision System
- Mark-on-the-Fly Technology

Controllers

U15 External PC

Software

Proprietary Merlin® II LS

Lens Configurations

Diameter	Marking Area				Working Clearance	
103 mm	2.56 in	x	2.56 in	65 mm x 65 mm	5.35 in	136 mm
160 mm	4.33 in	x	4.33 in	110 mm x 110 mm	8.58 in	218 mm
250 mm	6.10 in	x	6.10 in	155 mm x 155 mm	12.2 in	310 mm
255 mm	6.69 in	x	6.69 in	170 mm x 170 mm	12.36 in	314 mm



Dimensions

w/o Vari-Z™		w/ Vari-Z™		<div> <div>w/o Vari-Z™</div> <div>6.03 in</div> <div>153 mm</div> <div>w/ Vari-Z™</div> <div>7.43 in</div> <div>189 mm</div> </div>
6.7 in	170 mm	7.06 in	179 mm	
22.06 in		29.94 in		

w/o Vari-Z™		w/ Vari-Z™	
22.06 in	560 mm	29.94 in	760 mm

DUAL-HEAD

FIBER


VANADATE

GREEN

UV

CO₂

ENCLOSURES



For organic materials like wood, the CO₂ line of laser marking systems can't be beat.

CO₂-30

TELESIS
MARK OF CONFIDENCE


Proven Flexibility and Practicality

CO₂ LASER MARKING SYSTEM

Great for marking organic materials like wood, rubber, paper, and ceramic

Equally **capable at stationary bench-top use and mark-on-the-fly** installations

Excellent choice for **heavy industrial and high-duty cycle** applications



Models

CO₂ • 10 10 Watt

CO₂ • 30 30 Watt

Controllers

Model C1830EF Embedded PC

Technology Options

iZONIT™ Vision System

Mark-on-the-Fly Technology

Programmable Mounting Post

Software


Proprietary Merlin® II LS

Lens Configurations

Diameter	Marking Area				Working Clearance	
100 mm	2.76 in	x	2.76 in	70 mm x 70 mm	3.19 in	81 mm
160 mm	4.33 in	x	4.33 in	110 mm x 110 mm	5.15 in	131 mm
210 mm	5.51 in	x	5.51 in	140 mm x 140 mm	7.24 in	184 mm
350 mm	9.84 in	x	9.84 in	250 mm x 250 mm	13.82 in	351 mm



Dimensions



DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES

Technical Laser Matrix

MODEL	FIBER	ULTRAVIOLET		
	F30 / F50	UVC	UV/one	
MARK DESCRIPTION	Q-SWITCHED YTTERBIUM FIBER	FIBER-COUPLED DPSS	FIBER-COUPLED DPSS	
WAVE LENGTH	1060 NM	355 NM	355 NM	
AVERAGE POWER	UP TO 30 WATTS	UP TO 2 WATTS	UP TO 1 WATT	
PULSE FREQUENCY	30 - 120 KHZ + 50 - 120 KHZ			
POSITIONING	VISIBLE RED DIODE LIGHT	VISIBLE RED DIODE LIGHT	VISIBLE RED DIODE LIGHT	
LASER HEAD (IN) (LXWXH)	22.791 X 5.076 X 5.991	22.06 X 6.7 X 6.03	24.41 X 7.0 X 7.5	
LASER HEAD (MM) (LXWXH)	578.9 X 128.9 X 152.2	560 X 170 X 153	620 X 178 X 191	
VARI-Z HEAD (IN)	26.311 X 6.32 X 5.221	29.94 X 7.06 X 7.43		
VARI-Z HEAD (MM)	668.3 X 160.5 X 140.2	760 X 179 X 189		
LASER HEAD WEIGHT	16.84 LBS (7.64 KG)	46 LBS (20.8 KG)	32 LBS (14.5 KG)	
CONTROLLER	F14A, MODEL 6, F16I	U15	Integrated	
CONTROLLER (IN) (LXWXH)	20.12 X 17.25 X 8.38	10 X 16.74 X 5.53		
CONTROLLER (MM) (LXWXH)	511.048 X 438.2 X 212.7	254 X 425.19 X 140.46		
CONTROLLER WEIGHT	60 LBS (27.27 KG)	15 LBS (6.803 KG)		
LENS OPTIONS (IN) + MARKING WINDOW	100 MM 2.56 X 2.56 160 MM 3.54 X 3.54 163 MM 4.33 X 4.33 254 MM 6.89 X 6.89 330 MM 9.06 X 9.06 350 MM 9.84 X 9.84 420 MM 11.42 X 11.42	103 MM 1.96 X 1.96 160 MM 3.15 X 3.15 250 MM 6.10 X 6.10		
		103 MM 50 X 50 160 MM 80 X 80 250 MM 155 X 155		
LENS OPTIONS (MM) + MARKING WINDOW	100 MM 65 X 65 160 MM 90 X 90 163 MM 110 X 110 254 MM 175 X 175 330 MM 230 X 230 350 MM 250 X 250 420 MM 290 X 290			
RESOLUTION	16-BIT (LENS DEPENDENT)	16-BIT (LENS DEPENDENT)	16-BIT	
FONT	VECTOR, CUSTOM, TRUETYPE	VECTOR, CUSTOM, TRUETYPE	VECTOR, CUSTOM, TRUETYPE	
BARCODE	YES	YES	YES	
2D MATRIX CODE	YES	YES	YES	
GS1 DATA BAR	YES	YES	YES	
LOGO IMAGE	YES	YES	YES	
MACHINE OPERATION	MANUAL OR AUTOMATIC	MANUAL OR AUTOMATIC	MANUAL OR AUTOMATIC	
HEAD CABLE	2.74 M TO 5 M		ETHERNET CABLE	
COOLING	AIR COOLED, FAN	AIR COOLED	AIR COOLED	
MAX POWER CONSUMPTION	LESS THAN 280 WATTS	LESS THAN 400 WATTS	LESS THAN 280 WATTS	
OPERATING TEMP (F)	59° - 95° F	65° - 95° F	65° - 93° F	
OPERATING TEMP (C)	18° - 35° C	15° - 35° C	18° - 34° C	
RECOMMENDED TEMP (F)	68° - 77° F	68° - 77° F	68° - 77° F	
RECOMMENDED TEMP (C)	20° - 25° C	20° - 25° C	20° - 25° C	
AMBIENT HUMIDITY	10% - 85% NON-CONDENSING	10% - 85% NON-CONDENSING	10% - 85% NON-CONDENSING	
COMPLIANCE	CDRH, CE	CDRH, CE	CDRH, CE	
INTERFACE COMMUNICATION	TCP/IP, ETHERNET/IP, PROFINET DISCRETE IO	TCP/IP, ETHERNET/IP, PROFINET DISCRETE IO	TCP/IP, ETHERNET/IP, PROFINET DISCRETE IO	
SOFTWARE	MERLIN® II LS	MERLIN® II LS	MERLIN® II LS	
OPERATING SYSTEM	WINDOWS® 7 OR BETTER	WINDOWS® 7 OR BETTER	WINDOWS® 7 OR BETTER	
DIODE WARRANTY	2 YEARS	18 MONTHS	1 YEAR	
ELECTRONICS WARRANTY	1 YEAR	1 YEAR	1 YEAR	

CO2	VANADATE			GREEN
CO2 • 10 / Co2 • 30	EVCDS	EV15DS	EV40	EV4GDS
SEALED-TUBE, CARBON DIOXIDE 10.6 MICROMETERS (µM) 10 WATTS VISIBLE RED DIODE LIGHT	FIBER-COUPLED DPSS 1064 NM UP TO 15 WATTS VISIBLE RED DIODE LIGHT	FIBER-COUPLED DPSS 1064 NM UP TO 20 WATTS VISIBLE RED DIODE LIGHT	FIBER-COUPLED DPSS 1064 NM UP TO 55 WATTS VISIBLE RED DIODE LIGHT	FIBER-COUPLED DPSS 532 NM UP TO 10 WATTS VISIBLE RED DIODE LIGHT
34.03 X 8.301 X 8.52 864.4 X 210.8 X 216.6	24 X 6.1 X 5.55 610 X 154 X 141	28.3 X 6.4 X 7.5 719 X 162 X 191.6	29.3 X 8.8 X 9.3 743.1 X 223.7 X 235.6	31.73 X 9.783 X 7.44 805.95 X 248.49 X 196.68
56 LBS (25.4 KG)	32 LBS (14.5 KG)	44 LBS (20 KG)	44 LBS (20 KG)	55 LBS (25 KG)
C18 / C18E 18 X 17.340 X 5.53 457 X 440 X 140 22LBS (9.98KG)	E15 15.5 X 18.24 X 5.52 393.7 X 437.9 X 140.2 33 LBS (15 KG)	E15 15.5 X 18.24 X 5.52 393.7 X 437.9 X 140.2 33 LBS (15 KG)	E1140 17.3 X 8.3 X 17.3 439 X 211 X 438 38 LBS (17.3 KG)	E15 15.5 X 18.24 X 5.52 393.7 X 437.9 X 140.2 33 LBS (15 KG)
100 MM 2.76 X 2.76 160 MM 4.33 X 4.33 210 MM 5.51 X 5.51 350 MM 9.84 X 9.84	100 MM 2.56 X 2.56 160 MM 4.33 X 4.33 254 MM 6.89 X 6.89 330 MM 9.06 X 9.06 420 MM 11.42 X 11.42	100 MM 2.56 X 2.56 160 MM 4.33 X 4.33 163 MM 4.33 X 4.33 254 MM 6.89 X 6.89 330 MM 9.06 X 9.06 420 MM 11.42 X 11.42	100 MM 2.56 X 2.56 160 MM 3.54 X 3.54 163 MM 4.33 X 4.33 254 MM 6.89 X 6.89 330 MM 9.06 X 9.06 350 MM 9.84 X 9.84 420 MM 11.42 X 11.42	100 MM 2.17 X 2.17 160 MM 3.54 X 3.54 254 MM 6.69 X 6.69 330 MM 11.42 X 11.42
100 MM 70 X 70 160 MM 110 X 110 210 MM 140 X 140 350 MM 250 X 250	100 MM 65 X 65 160 MM 110 X 110 254 MM 175 X 175 330 MM 230 X 230 420 MM 290 X 290	100 MM 65 X 65 160 MM 110 X 110 163 MM 110 X 110 254 MM 175 X 175 330 MM 230 X 230 420 MM 290 X 290	100 MM 65 X 65 160 MM 90 X 90 163 MM 110 X 110 254 MM 175 X 175 330 MM 230 X 230 350 MM 250 X 250 420 MM 290 X 290	100 MM 55 X 55 160 MM 90 X 90 254 MM 175 X 175 420 MM 290 X 290
16-BIT (LENS DEPENDENT) VECTOR, CUSTOM, TRUETYPE YES YES YES YES MANUAL OR AUTOMATIC	16-BIT (LENS DEPENDENT) VECTOR, CUSTOM, TRUETYPE YES YES YES YES MANUAL OR AUTOMATIC	16-BIT VECTOR, CUSTOM, TRUETYPE YES YES YES YES MANUAL OR AUTOMATIC	16-BIT VECTOR, CUSTOM, TRUETYPE YES YES YES YES MANUAL OR AUTOMATIC	16-BIT VECTOR, CUSTOM, TRUETYPE YES YES YES YES MANUAL OR AUTOMATIC
1.8 M AIR-COOLED, FANS LESS THAN 680 WATTS	1.75 M OR 4.75 M AIR COOLED, ACTIVE LESS THAN 400 WATTS	1.75 M OR 4.75 M AIR COOLED, ACTIVE LESS THAN 500 WATTS	1.75 M OR 4.75 M AIR COOLED, ACTIVE LESS THAN 950 WATTS	1.75 M OR 4.75 M AIR COOLED, ACTIVE LESS THAN 600 WATTS
59°F TO 86°F 15°C TO 30°C 61°F TO 75°F 16°C TO 24°C 10% TO 90% NON-CONDENSING	59° - 95° F 15° - 35° C 68° - 77° F 20° - 25° C 10% - 85% NON-CONDENSING	65° - 95° F 18° - 35° C 68° - 77° F 20° - 25° C 10% - 85% NON-CONDENSING	65° - 95° F 18° - 35° C 68° - 77° F 20° - 25° C 10% - 85% NON-CONDENSING	59° - 95° F 15° - 35° C 68° - 77° F 20° - 25° C 10% - 85% NON-CONDENSING
CDRH ETHERNET IP, PROFINET, TCP/IP, SERIAL	CDRH, CE TCP/IP, ETHERNET/IP, DISCRETE IO	CDRH, CE TCP/IP, ETHERNET/IP, DISCRETE IO	CDRH, CE TCP/IP, ETHERNET/IP, DISCRETE IO	CDRH, CE TCP/IP, ETHERNET/IP, DISCRETE IO
MERLIN® II LS WINDOWS® 7 OR BETTER 1 YEAR 1 YEAR	MERLIN® II LS WINDOWS® 7 OR BETTER 2 YEARS 1 YEAR	MERLIN® II LS WINDOWS® 7 OR BETTER 2 YEARS 1 YEAR	MERLIN® II LS WINDOWS® 7 OR BETTER 2 YEARS 1 YEAR	MERLIN® II LS WINDOWS® 7 OR BETTER 2 YEARS 1 YEAR



PROSTATION™ // Class 1 Laser Enclosure

- DURABLE**
Constructed with industrial grade materials
- FLEXIBLE**
Accommodates an array of part shapes and sizes
- SAFE**
Complies with CDRH Class 1 and ISO13849-1 guidelines
- EFFICIENT**
Engineered for rapid processing



ProStation™

Why it's great

Robust, industrial, and customizable Class 1 laser enclosure for marking large parts

Enclosure Size
W x H x D

40 in x 102.5 in x 40.24 in
1016 mm x 2603 mm x 1022 mm

Interior Working Area
W x H x D

36.5 in x 37 in x 30.25 in
927 mm x 940 mm x 768 mm

Mini ProStation™

Narrow and nimble Class 1 enclosure workstation **for challenging space constraints**

27.5 in x 71.3 in x 35.4 in
698 mm x 1811 mm x 899 mm

26.5 in x 36.5 in x 24.5 in
673 mm x 927 mm x 622 mm

DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES

Class 1 Laser Enclosures



DialPro™

// FASTER CYCLE TIME

Simultaneous load/unload and mark/read operations with dual positions

Concurrently run multiple processes in parallel with the addition of extra positions

// INCREASED PRODUCTIVITY

Fast and easy part handling with integration-friendly front or overhead load/unload design

Time-saving view of control operations and code reading with overhead monitor

Greater mark positioning efficiency and 2D code reading functionality

// APPLICATION FLEXIBILITY

Accommodates a variety of process options including 3D marking, code reading, inspection, cleaning

36 in (914 mm) diameter dial table and a 10 in (254 mm) height clearance provide ample spatial capacity for processing a wide range of part sizes



BoxPro™

// PLUG AND PLAY

The Telesis BoxPro arrives fully assembled, meaning once it is powered, you can get right to work

// SIMPLICITY PERFECTED

The BoxPro offers a simple effective design paired with an entry-level laser marker perfect for smaller and up-and-coming outfits

// RIGHT-SIZED

At 20 in x 16 in (508 mm x 406.4 mm) this efficiently sized Class 1 enclosure can fit into almost any production space.



ProMed™

// MEDICAL GRADE


The Telesis ProMed is exclusively designed for the demanding needs of medical device part marking

// PRECISION IN MIND

The Mattison precision ground top plate, Aerotech X/Y stage, heavy-duty welded steel base, and robust programmable Z-axis mounting post make this equipment solid and marks exact

// LASER FOCUSED

Equipped with a laser perfect for annealing as well as other applications, the Telesis ProMed is available as a Class 1 or CDRH Class 4 enclosure



DUAL-HEAD

FIBER

VANADATE

GREEN

UV

CO₂

ENCLOSURES



PINSTAMP[®]

Dot Peen Markers

PINSTAMP® Marker Overview

Page **34**

Popular PINSTAMP® Markers

Page **39**

PINSTAMP® Controllers

Page **46**

Telescribe® Marking Systems Overview

Page **47**

PINSTAMP® Details

Page **48**

"What separates Telesis from the others is the way they believe in and stand behind their products. Telesis delivers."

- Jeremy Tinchler, Smith & Nephew

PINSTAMP® Dot Peen Overview

SINGLE-PIN DOT PEEN MARKERS

	TMP1700	TMP2100	TMP3200	TMP4210	TMP4750	TMP6100
						
Features	This proven industrial workhorse is an industry staple and continues to impress.	The TMP2100 provides great functionality fit into a smaller footprint.	A generously sized marking window sets this dot peen marker apart from the rest.	The TMP4210 is an incredibly lightweight and compact hand-held marker.	This lightweight hand-held marker delivers remarkable power and depth.	The robotic design delivers precise marks and makes part placement easy.
What it's Good For	Field-Proven Design Highly Functional Unparalleled Reliability	Fast Marking Small Characters Compact Envelope	Fast Marking For Constrained Space Robust Construction	For High Production Space Constraints Easy to Use	VIN Marking Extra-Deep Marking Dark Spaces	Large Applications Cylindrical Marking Medical Applications
Marking Window (in)	1.50 in x 2.50 in	0.79 in x 1.96 in	4.0 in x 6.0 in	0.5 in x 2.0 in	1.57 in x 5.5 in	6.0 in x 12.0 in
Marking Window (mm)	38 mm x 63 mm	20 mm x 50 mm	100 mm x 150 mm	13 mm x 51 mm	40 mm x 140 mm	152 mm x 305 mm
Max Marking Speed	5 characters / second	4 characters / second	4 characters / second	4 characters / second	4 characters / second	2 characters / second
Marking Depth (in)	0.001 - 0.013 in	0.001 - 0.013 in	0.003 - 0.013 in	0.001 - 0.013 in	0.001 - 0.018 in	0.001 - 0.018 in
Marking Depth (mm)	0.076 - 0.305 mm	0.03 - 0.33 mm	0.03 - 0.33 mm	0.03 - 0.33 mm	0.03 - 0.45 mm	Varies
Max Character Height (in)	1.5 in	0.79 in	4.0 in	0.5 in	5.5 in	6 in
Max Character Height (mm)	38 mm	20 mm	101.6 mm	12.7 mm	140 mm	152.4 mm
Max Resolution	200 dpi	200 dpi	200 dpi	200 dpi	200 dpi	200 dpi
Logo Marking Capable	Yes	Yes	Yes	Yes	Yes	Yes
2D Code Marking Capable	Yes	Yes	Yes	Yes	Yes	Yes
Radial Marking Capable	Yes	Yes	Yes	No	No	Yes
Programmable Z-Axis	Yes	Yes	Yes	Yes	No	Yes
Floating Pin Technology	Yes	Yes	Yes	Yes	Yes	Yes
Maximum Number of Pins	1	1	1	1	1	1
Mounting	Fixtured Standard Handheld Optional	Fixtured Standard Handheld Optional	Fixtured Standard Handheld Optional	Handheld Standard Fixtured Optional	Handheld Standard Fixtured Optional	Fixtured Standard
Available in Electric	Yes	No	Yes	No	No	No
Controllers Available	Fixed Button (TMC470) Touch Screen (TMC520) Merlin III w/ PC	Fixed Button (TMC470) Merlin III w/ PC	Fixed Button (TMC470) Merlin III w/ PC	Fixed Button (TMC470) Merlin III w/ PC	Fixed Button (TMC470) Touch Screen (TMC520) Merlin III w/ PC	Fixed Button (TMC470) Merlin III w/ PC

MULTI-PIN DOT PEEN MARKERS

PORTABLE DOT PEEN MARKERS

TMM4200

TMM4250

TMP4500E

Nomad 2000

Nomad 4000



A unique, compact ergonomic multi-pin marker is incredibly fast.

Ideal for online applications in wet, dirty manufacturing environments.

A powerful piece of hand-held equipment, this marker eliminates the need for air.

The Nomad 2000 is a fully portable, rechargeable, battery-powered system.

The Nomad 4000 is a fully portable, rechargeable, with more power than the 2000.

Constrained Space
Comfortable Grip
Makes Quick Marks

Wet Environments
Fixture Applications
For Constrained Space

Does Not Require Air
Makes Deep Marks
Easy to Hold

Rechargeable Battery
Can Go Anywhere
Does Not Require Air

Makes Deep Marks
Can Go Anywhere
Does Not Require Air

0.5 in x 2.0 in

0.5 in x 2.0 in

1.0 in x 4.0 in

1.0 in x 4.0 in

1.0 in x 4.0 in

12.7 mm x 50.8 mm

12.5 mm x 60.8 mm

25.4 mm x 101.6 mm

25.4 mm x 101.6 mm

25.4 mm x 101.6 mm

8 Characters / second

8 Characters / second

4 characters / second

2 characters / second

2 characters / second

0.001 - 0.013 in

0.001 - 0.013 in

0.001 - 0.018 in

0.001 - 0.010 in

0.001 - 0.018 in

0.03 - 0.33 mm

0.03 - 0.33 mm

0.03 - 0.46 mm

0.03 - 0.25 mm

0.03 - 0.46 mm

0.5 in

0.5 in

1.0 in

1.0 in

1.0 in

12.7 mm

12.7 mm

25.4 mm

25.4 mm

25.4 mm

200 dpi

200 dpi

80 dpi

80 dpi

80 dpi

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

No

Yes

No

No

No

No

No

No

No

No

Yes

Yes

No

No

No

4

4

1

1

1

Handheld Standard

Handheld Standard

Handheld Standard

Handheld Standard

Handheld Standard

No

No

Electric Only

Electric Only

Electric Only

Fixed Button (TMC470)
Merlin III w/ PC

Fixed Button (TMC470)
Merlin III w/ PC

Fixed Button (TMC470)
Merlin III w/ PC

Nomad Controller

Nomad Controller

* Speed based on
.125 in (3 mm) characters

ENTRY LEVEL DOT PEEN MARKERS

BenchMark® 200



BenchMark® 320



BenchMark® 460



Features	An entry-level system with extruded aluminum marking head mounting post and base	An entry-level machine good for bench-top applications and stand-alone marking.	An entry-level fully programmable machine great for portable marking.
What it's Good For	Smaller Budgets Does Not Require Air Great Value	Smaller Budgets Does Not Require Air Great Value	Smaller Budgets Does Not Require Air Great Value
Marking Window (in)	4.0 in x 4.0 in	4.0 in x 6.0 in	1.0 in x 4.0 in
Marking Window (mm)	101 mm x 101 mm	101 mm x 152.4 mm	25 mm x 101 mm
Max Marking Speed	3 characters / second	3 characters / second	3 characters / second
Marking Depth (in)	0.001 - 0.010 in	0.001 - 0.018 in	0.001 - 0.010 in
Marking Depth (mm)	0.03 - 0.25 mm	0.03 - 0.46 mm	0.03 - 0.25 mm
Max Character Height (in)	4.0 in	4.0 in	1.0 in
Max Character Height (mm)	101.6 mm	101.6 mm	25.4 mm
Max Resolution	80 dpi	75 dpi	80 dpi
Logo Marking Capable	Yes	Yes	Yes
2D Code Marking Capable	Yes	Yes	Yes
Radial Marking Capable	No	Yes	No
Programmable Z-Axis	No	No	No
Floating Pin Technology	No	No	No
Maximum Number of Pins Mounting	1	1	1
Available in Electric	Electric Only	Electric Only	Electric Only
Controllers Available	Fixed Button (BM470) Touch Screen (TMC520)	Fixed Button (BM470) Touch Screen (TMC520) Merlin III w/ PC	Fixed Button (BM470) Touch Screen (TMC520)

Speed >>

Depth >>

Flexibility >>

Meeting Every Challenge

THE WORLD'S **FASTEST** DOT PEEN **MARKER**

Speed up to
16 characters
per second



Unique to Telesis, our PINSTAMP® dot peen markers **have multiple pins to complete marks more quickly.** From 2 pins to 8 pins, we have a solution that meets your needs. The TMM5400, with 8 pins, is the world's fastest marker. The TMM5100 is also a versatile option for speed.

MULTI- **STRIKE**

Depths up to
.022 in
.5588 mm



The proprietary Multi-Strike feature fires the pin multiple times, resulting in a deeper mark. The software upgrade can be added to many markers. The TMM7200 is a custom product for extra deep marking needs.



Barcode Scanner



AutoSense



Rotary Chuck



Programmable Z-Axis



iZONIT™

TELESIS® PINSTAMP®

TMP1700
MARKING SYSTEM

The Proven Industrial Workhorse

TMP1700

Rugged, low-maintenance X/Y platform

Compact, contaminant-resistant head design

Marks a wide range of materials from soft plastics to hardened steel (rc60)

Interchangeable marking pin sizes for depths from 0.001 in - 0.018 in (0.03 mm - 0.45 mm)

Floating pin technology easily **accommodates surface irregularities** up to 0.25 in (6 mm)

Additional Features

- TMP1700EAS: Available as electric model
- Marking speeds up to five characters per second
- Automatically generates serial numbers, time, date, and shift codes
- Store hundreds of marking patterns
- Easily interfaced to PLCs and host computers

Controllers

- Fixed Button** (TMC470)
- Touch Screen** (TMC520)
- PC with Merlin® III**

Software

- Proprietary **Merlin® III** (optional)



Options and Accessories


- Rotary fixtures for marking circumferences of cylindrical parts
- Marking head mounting post, including programmable Z-axis
- Panel-mount and IP/NEMA rated controllers
- Easy and free software upgrades

Marking Window



Marking Specifications

Max Character Depth	0.003 in 0.76 mm
Max Character Height	1.5 in 38.1 mm
Characters per Second	5
Resolution	200 dpi



TELESIS[®] PINSTAMP[®]

TMP3200

MARKING SYSTEM

A Large Marking Window

TMP3200

- Simple yet robust** belt-driven dual rail
- X/Y platform yields **high-quality characters**
- Rugged design means **long-lasting, low-maintenance operation**
- Marks a wide range of materials** from soft plastics to hardened steel (rc60)
- Floating pin technology easily **accommodates surface irregularities** up to 0.25 in (6 mm)

Additional Features

- TMP3200EAS: Available as electric model
- Dot Density: Up to 200 dots-per-inch (79 dots per centimeter)
- Choice of interchangeable marking pins: .001 in - .018 in (0.03 mm - 0.34 mm)
- Marking speeds up to four characters per second
- Automatically generates serial numbers, time, date, and shift codes

Controllers

- Fixed Button** (TMC470)
- Touch Screen** (TMC520)
- PC with Merlin® III**

Software

- Proprietary **Merlin® III** (optional)



Options and Accessories


- Rotary fixtures for marking circumferences of cylindrical parts
- Marking head mounting post, including programmable Z-axis
- Panel-mount and IP/NEMA-rated controllers
- Easy and free software upgrades


Marking Window



Marking Specifications

Max Character Depth	0.013 in 0.33 mm
Max Character Height	4.0 in 101.6 mm
Characters per Second	4
Resolution	200 dpi





TELESIS® PINSTAMP®

TMP4210
MARKING SYSTEM

1893808

Lightweight and Compact Handheld

TMP4210

Great for smaller environments where movement and space are restricted

Lightweight construction makes the marker **easy to hold** for long periods of time

Durable components **withstand tough manufacturing environments**

Satisfies a wide range of applications **either as a portable handheld marker or integrated**



Additional Features

- Dot Density: Up to 200 dots-per-inch (79 dots per centimeter)
- Choice of interchangeable marking pins: .001 in - .018 in (0.03 mm - 0.34 mm)
- Marking speeds up to four characters per second
- Automatically generates serial numbers, time, date, and shift codes
- Easily interfaced to PLCs and host computers

Controllers

- Fixed Button (TMC470)
- Touch Screen (TMC520)
- PC with Merlin® III


Software

- Proprietary Merlin® III (optional)

Options and Accessories

- Quick-Disconnect tool post
- Multi-Strike
- Panel-mount and IP/NEMA-rated controllers
- Easy and free software upgrades

Marking Window



Marking Specifications

Max Character Depth	0.013 in 0.3 mm
Max Character Height	0.5 in 12.7 mm
Characters per Second	4
Resolution	200 dpi





"The 6100 is top quality. Our markers run all day long and they are bulletproof."

- Bud Nelson, Acutec Precision

Robotic Design for Precise Marks

TMP6100 (TMP6100EAS)

Great for cylindrical marking where a rotary device can add efficiency and practicality

Durable components **withstand tough manufacturing environments**

Satisfies a wide range of marking applications while **integrating into factory automation networks**

AutoSense motorized Z-Axis mounting post ensures **consistent pin stroke and critical standoff distance is consistently repeated**

Additional Features

- TMP6100EAS: Available as electric model
- Choice of interchangeable marking pins: .001 in - .018 in (0.03 mm - 0.34 mm)
- Marking speeds up to two characters per second
- Automatically generates serial numbers, time, date, and shift codes
- Easily interfaced to PLCs and host computers

Controllers

Fixed Button (TMC470)

Software

Proprietary **Merlin® III** (optional)

Options and Accessories


- Rotary fixtures for marking cylindrical parts
- Marking head mounting post, including programmable Z-axis
- Panel-mount and IP/NEMA-rated controllers
- Easy and free software upgrades

Marking Window



Marking Specifications

Max Character Depth	Varies
Max Character Height	6 in 152.4 mm
Characters per Second	2
Resolution	200 dpi



PINSTAMP® Controllers



TMC470 Fixed Button Controller

- Fully contained controller—no PC required
- Easy-to-use menu design for pattern design
- Ethernet port for TCP/IP communications
- EthernetIP and PROFINET capable
- Durable membrane keyboard
- Store up to 400 marking patterns locally
- Panel-mount kits available
- Software can be customized for unique applications

TMC520 FEATURES



TMC520 Touch Screen Controller

- Create a design and produce a mark in under a minute
- See exactly how the design will look before printing
- Easy-to-use tools for arc text, graphics, and data matrix
- Contaminant-resistant design and flexible installation
- Software can be customized for unique applications
- Impact-resistant touch screen interface
- Panel-mount and stand kits available
- Simple menu design for pattern design
- Ethernet IP and Profinet capable




PINCH ZOOM



PARSE FLAGS



ARC TEXT



EASY SWIPE MENUS

SC2000



The SC2000 is a great **low-noise compact marker** for continuous marking of human-readable characters and symbols

SS3700



The SS3700 is expertly designed with a **large marking window and creates deep, quick marks with a servo-driven motor**

SC5000



A powerful scribe marker, the **heavy duty SC5000 has a large marking window and can create extra deep and wide marks**

SC6000VIN



A scribe marker specifically designed to mark VINs, the **heavy duty SC6000VIN exceeds deep marking regulations and requirements**

SC2000 Marking Window

2.95 in x 1.57 in
(75 mm x 40 mm)

Marking Speed

.125 in (3 mm) character
up to 2 characters/second

SS3700 Marking Window

2 in x 6 in
(50.8 mm x 152.4 mm)

Marking Speed

.276 in (7 mm) character
up to 4 characters/second

SC5000 Marking Window

2.5 in x 7.5 in
(63 mm x 190 mm)

Marking Speed

.125 in (3 mm) character
up to 2 characters/second

SC6000VIN Marking Window

1.18 in x 6.5 in
(30 mm x 165.1 mm)

Marking Speed

.18 in (4.5 mm) character
up to 2.0 characters/second

TELESCRIBE® FEATURES




A **wide variety** of marking pins are available

Easily integrates into a wide range of automated online and manual applications

Virtually silent marking

Pin **penetrates without puncture**

Produces **crisp** logos in addition to text



PINSTAMP® Marking Windows Comparison

TMP6100

6.0 in x 12.0 in

152.4 mm x 304.8 mm

TMP3200

4.0 in x 6.0 in

101.6 mm x 152.4 mm

Benchmark 320

4.0 in x 6.0 in

101.6 mm x 152.4 mm

Floating Pin

PINSTAMP® pneumatic dot peen markers contain our **revolutionary floating pin technology, developed and patented by Telesis**. This technology enables PINSTAMP® marking systems to accommodate surface irregularities up to .25 in (6 mm) and mark clearly and reliably on many types of materials.

// Give the user the ability to make adjustments to marks

// No springs to replace

// Constant positive air flow keeps in chamber clean

// Achieves higher speeds

RETURN AIR

DRIVE AIR



TMP4750

1.57 in x 5.5 in
40 mm x 140 mm

TMM4500E

1.0 in x 4.0 in
25.4 mm x 101.6 mm

NOMAD 2000

1.0 in x 4.0 in
25.4 mm x 101.6 mm

NOMAD 4000

1.0 in x 4.0 in
25.4 mm x 101.6 mm

Benchmark 460

1.0 in x 4.0 in
25.4 mm x 101.6 mm

TMP1700

1.50 in x 2.50 in
38.1 mm x 63.5 mm

TMP4210

0.5 in x 2.0 in
13 mm x 50.8 mm

TMM4200

0.5 in x 2.0 in
12 mm x 50 mm

TMP2100

0.79 in x 1.96 in
20 mm x 50 mm

TMM4250

0.5 in x 2.0 in
12 mm x 60 mm

The Telesis Advantage*



Vision Systems

Page **52**

Telesis Applications Lab

Page **54**

Merlin® Proprietary Software

Page **55**

Custom Engineered Solutions

Page **56**

Customer Service and Support

Page **57**

Robotics/AI Integration

Page **58**

****What our
competitors
can't match.***

iZONIT™ Laser Marking Vision System

Accurately and easily **establish and view mark positioning** before firing the laser

Set the mark location when the object to be marked is not visible

- Dial-indexing table enclosures
- Class 1 safety enclosures
- Remote marking operations

Save time and increase productivity during pattern design with a camera-assisted mark positioning system



Increase throughput—especially with marking applications that involve multiple parts or a variety of parts

Immediately verify and validate data matrix 2D codes for compliance

Also available for
PINSTAMP® Dot Peen
Marking Systems



Teleview™



Mark // Read // Verify

// Easily Automate Quality Control

// Integrated Camera Instantly Reads Marks

// Software Quickly Analyzes Code Integrity

// Real-time Verification Eliminates Wasted Parts

// Virtually Removes Human Errors

// Great for Intricate Part Marking


**TELE
VIEW**

Telesis Applications Lab


At the core of every customer interaction is the Telesis Applications Lab: **a team of marking experts dedicated to helping you purchase your equipment with confidence.**

They'll find the **most efficient and cost-effective piece of equipment** you need to make a beautiful and successful permanent mark.

Not sure what laser you need? Our team will determine what is right for you—and provide extensive recommendations—free of charge.



Merlin[®] Proprietary Software



Telesis Merlin[®] is powerful software that is capable of driving and operating all Telesis PINSTAMP[®] Dot Peen and Laser Marking Systems.

SAFE, EASY OPERATOR INTERFACE

Pattern design is made quick and easy with a simple interface for the creation and execution of machine- and human-readable marks. The Pattern Wizard Mode makes simple pattern design a snap even for a novice. Immediately adjust the size, location, and orientation of your mark designs.

MAKES EVERY MARK EASIER


Use Merlin[®] to create text strings, geometric shapes, graphics, and machine-readable data matrix symbols, alphanumeric characters, symbols, special message flags (serial numbers, times, dates, and user-defined codes), or import DXF files.

CONTROL ALL OF YOUR OPERATIONS FROM ONE SOFTWARE PLATFORM


Using Merlin[®] II LS, Merlin[®] Touch PS, and Merlin[®] III, your operators can maintain their comfort level and their efficiency by using the same interface across all of the Telesis Dot Peen and Laser equipment in your facility.

AUTOMATED MARKING INTERFACE

Merlin[®] II LS can be configured with AMI, creating a safe, easy, and operator interface: scan a barcode to load patterns, load a picture of the part and fixture, and insert the marking data in the proper field all without a keyboard—virtually mistake free.



UNEQUALED CUSTOM ENGINEERED SOLUTIONS



"The service department has been all we could ask for from a technical and assistance standpoint—a pleasure to deal with which is always an appreciated benefit."

- Chris Shetler, PixlMediaServices, Inc.



If our broad range of standard equipment doesn't suit your needs, we will **customize laser and dot peen systems to meet the most challenging production requirements.**




TOTALLY TURN KEY



CUSTOM SOLUTIONS FOR


- ✓ Demanding Cycle Time
- ✓ Difficult Locations
- ✓ Automated Processes
- ✓ Mark-on-the-Fly





All of our systems—
hardware and software—
are designed and
built in-house at our
state-of-the-art R&D and
manufacturing facilities in
California and Ohio, USA.




LEGENDARY
SERVICE
AND SUPPORT



Careful attention
to quality **ensures**
reliability through
the life of your
marking system.



ON-SITE
INSTALLATION
& STARTUP



Robotics/AI/Industry 4.0

Automated marking solutions are the future of the industry. Automation makes production consistent and efficient. The reliability of **industrial automation perfectly matches Telesis' rugged and durable products.**

// Great for managing full control of Z-axis focusing as well as **rotational control and location** for the laser marking process

// **Incorporates with vision systems** to inspect the mark or to use the system for cutting or welding

// Robotics **can perform functions where humans would be in danger**, creating a much safer options for challenging tasks

// High-volume marking applications are difficult for the operator to **provide consistency and repeatability**, and could present ergonomic challenges for human workers

// Telesis robotic integration is **ideal for medical clean rooms** with no human interactions with the parts at all. The part can be picked up and inspected by the robot with **no risk of contamination**



Global Presence, Local Solutions

WORLDWIDE SALES & SERVICE

telesis.com
sales@telesistech.com
800-654-5696

CIRCLEVILLE

Corporate Headquarters
28181 River Drive
Circleville, Ohio 43113

+1 740 477 5000
sales@telesistech.com

THE NETHERLANDS

European Headquarters
+31 (0)88 505 1800
sales-europe@telesistech.com

Leeuwenhoekstraat 80
2652 XL Berkel en Rodenrijs

FREMONT

48377 Fremont Blvd #115
Fremont, CA 94538

LOS ANGELES

2512 Artesia Blvd, Unit 260C
Redondo Beach, CA 92078

NASHVILLE

2070 Lebanon Road
Lebanon, TN 37087

GERMANY

+49 (0)2191/609080
info@telesis-gmbh.de

Wulfingstrasse 6
D-42477 Radevormwald

RUSSIA

+7 (343) 287-46-27
sales-sng@Telesis.ru

CHINA

+86-21-3390-1806
sales@telesischina.com

3000 Long Dong Ave
Bldg. 1-402, Pudong New Area
Shanghai, 201203

UNITED KINGDOM

+44 (0)1404 549139
uksales@telesistech.com

Unit 2 Diamond House,
Reme Drive,
Heathpark Industrial Estate,
Honiton, Devon EX14 1SE

**TELESIS WORKS EVERY DAY TO
WOW OUR CUSTOMERS
AT EACH STEP**

OF THEIR PERMANENT MARKING AND TRACEABILITY JOURNEY

TO DO THIS, WE DELIVER
THE ULTIMATE CUSTOMER EXPERIENCE,
CREATE ROBUST, SOLID,
LONG-LASTING PRODUCTS
AND PROVIDE EXPERT
END-TO-END SOLUTIONS